

Hacı Sabancı
Organize Sanayi Bölgesi,
Celal Bayar Bulv. No:8
Sarıçam, Adana, Türkiye
+90 322 394 39 00
info@ceylift.com
www.ceylift.com

CEYLIFT CY45D TECHNICAL SPECIFICATIONS

	DEFINITION	UNIT	CY45D
Identification	Producer		Ceytech Makina San.Ve Tic.A.Ş.
	Origin		Turkey
	Power Type		Diesel
	Load Capacity/ Rated Load	kg	4500
	Load Center Distance	mm	500
	Wheelbase	mm	2000
Weights	Service Weight	kg	6820
	Axle loading, loaded front/rear	Kg	9935/1385
	Axle loading, unloaded front/rear	Кg	2760/4060
Wheels, Chassis	Tires: solid rubber (V), pneumatic (P)		Р
	Tires size front		300-15
	Tires size rear		7.00-12
	Wheels number front, rear (x= driven wheels)		2/2
	Tread, front/rear	mm	1150/1135
Basic Dimentions	Mast/fork carriage tilt forward/backward	degrees	6°/12°
	Lowered mast height	mm	3046
	Free Lift	mm	155
	Lifting Height	mm	4500
	Extended Mast Height	mm	5700
	Overhead load guard (cab) height	mm	2310
	Overall Length	mm	4520
	Length to face of forks	mm	3320
	Overall Width	mm	1450
	Fork Dimentions	TxWxL mm	50 x150 x 1200
	Fork Carriage Width	mm	1350
	Ground clearance, loaded, under mast	mm	150
	Ground clearance, centre of wheelbase	mm	205
	Aisle width for pallets 1000 x 1200 crossways	mm	4480
	Turning Radius	mm Km /h	2850
Performance Data	Travel Speed, loaded/unloaded Lifting Speed, loaded/unloaded	Km /h	23/24 350/430
	Lowering Speed, loaded/unloaded	mm / s mm /s	500/450
	Max Gradebitily Loaded	%	30
	Battery Voltage/Capacity	V/Ah	12 / 105
	Parking Brake Operation/ Control	•// •	EI / ELECTRO HYDROLIC
Engine	Marker		TÜMOSAN
	Model		TÜMOSAN 4DT
	Rated Output,SAE net	Hp/kW	85 / 62
	Max. Torque, SAE net	пр/кw Nm@min-1	340
	Rated RPM	Min-1	J+0
Other Details	Type of drive control	14111-T	Powershift
	Fuel Tank Capacity	L	98
		L	50

